CAT. N° 4 117 17

RCCB TX³ - 4P 400 V~ - 100 MA - 25 A - AC TYPE

Pack (number of units)	1
Volume (dm³)	0,701
Weight (g)	337,00

Product characteristics

4-pole 400 V~
- Neutral on right-hand side

AC type
- Sensitivity : 100 mA
- In : 25 A
- Number of modules : 4

General characteristics

RCCBs TX³ residual current circuit breakers - from 16 A to 80 A - AC and A types
- Conform to IEC 61008-1
- Compatible with prong-type and fork type supply busbars
- AC type : detect AC component faults
- A type : detect AC and DC component faults

Documentation

Catalogue pages & additional information
- Description page (p.054)
- Dimensions of din-rail equipment

Agreements & certificates of conformity
- VDE-40041193
- OC / CB-CB FR_705078
- OC / CB-CB-FR_700757
- VDE-40041193

Installation & technical data
- F01576EN-03

Environmental product profile
- LGRP-00366-V02

* All prices given are the manufacturer's list prices for professional customers, and are given for information only. They are not to be considered as a mandatory retail price - Basis : before-tax price list, May 2018

The information given in this e-catalogue (characteristics and dimensions) may be amended, and therefore does not represent an undertaking on our part. The e-catalogue is reserved for professionals only. You are also reminded that all products must be installed by a qualified professional in accordance with the installation rules.